

200310701-1

10/648,122

IN THE CLAIMS:

Please amend the claims as follows:

1. (currently amended) A method for creating a three-dimensional solid freeform fabrication object with non-reactive powder comprising:
spreading a non-reactive powder on a substrate;
selectively dispensing a reactive resin directly onto said non-reactive powder, forming a mixture of reactive resin and non-reactive powder, wherein said mixture defines said three-dimensional object; and
curing said reactive resin thereby encapsulating said non-reactive powder.
2. (currently amended) A method for creating a three-dimensional solid freeform fabrication object with non-reactive powder comprising:
spreading a non-reactive powder on a substrate;
~~The method of claim 1, further comprising heating said a reactive resin to a~~ temperature of about 40 to 200 degrees Celsius (C);
selectively dispensing said heated reactive resin onto said non-reactive powder,
forming a mixture of reactive resin and non-reactive powder, wherein said mixture defines said three-dimensional object; and
curing said reactive resin thereby encapsulating said non-reactive powder.
3. (currently amended) A method for creating a three-dimensional solid freeform fabrication object with non-reactive powder comprising:
spreading a non-reactive powder on a substrate;
selectively dispensing a reactive resin onto said non-reactive powder, forming a mixture of reactive resin and non-reactive powder, wherein said mixture defines said three-dimensional object;
~~The method of claim 1, further comprising applying ultrasonic energy to said mixture of reactive resin and non-reactive powder; and~~
curing said reactive resin thereby encapsulating said non-reactive powder.

200310701-1

10/648,122

4. (original) The method of claim 1, further comprising adding color to said reactive resin.
5. (original) The method of claim 1, wherein said reactive resin comprises a one-part reactive resin.
6. (original) The method of claim 5, wherein said one-part reactive resin comprises an ultraviolet (UV) curable resin.
7. (original) The method of claim 6, wherein said curing comprises applying UV radiation to said reactive resin.
8. (original) The method of claim 7, wherein said dispensing comprises selectively depositing a quantity of said one part reactive resin onto said non-reactive powder.
9. (original) The method of claim 1, wherein said reactive resin comprises a two-part reactive resin including a reactive build material and a curing agent.
10. (original) The method of claim 9, wherein said dispensing comprises: dispensing a layer of said reactive build material; and dispensing a layer of said curing agent.
11. (original) The method of claim 9, wherein said dispensing comprises simultaneously dispensing said reactive build material and said curing agent.
12. (original) The method of claim 9, wherein:
said reactive build material comprises an epoxy; and
said curing agent comprises a material from one of a amino group, a hydroxyl group, or a carboxyl group.

200310701-1

10/648,122

13. (original) The method of claim 9, wherein:
said reactive build material comprises a polyisocyanate; and
said curing agent comprises a polyol.
14. (original) The method of claim 9, wherein:
said reactive build material comprises a functionalized silicone; and
said curing agent is configured to react with a functional group on said silicone.
15. (original) The method of claim 9, wherein:
said reactive build material comprises prepolymers with unsaturated functionality; and
said curing agent comprises a free-radical cure curing agent.
16. (original) The method of claim 1, wherein said reactive resin comprises a
two-part UV curable resin including a UV initiator and a build material.
17. (original) The method of claim 16, wherein said selectively dispensing
comprises:
dispensing a layer of build material on said non-reactive powder; and
dispensing a layer of said UV initiator.
18. (original) The method of claim 16, wherein said selectively dispensing
comprises simultaneously dispensing said build material and said UV initiator.
19. (original) The method of claim 16, wherein said UV initiator is dissolved
in a solvent.
20. (original) The method of claim 19, wherein said solvent comprises a
monofunctional monomer.
21. (original) The method of claim 16, wherein said build material comprises
one of an acrylic compound, a compound having an epoxy substituent, a vinyl ether
substituent, vinylcaprolactam, vinylpyrrolidone, or urethanes.

200310701-1

10/648,122

22. (original) The method of claim 16, wherein said UV initiator comprises one of a free radical initiator or a cationic initiator.

23. (original) The method of claim 1, wherein said non-reactive powder comprises one of silica particles, glass spheres, metal powders, polymer powders, ceramic powders, or magnetic powders.

24. (currently amended) A solid freeform fabrication system for producing a three-dimensional object using non-reactive powder comprising:

a powder spreading system configured to spread a specified quantity of non-reactive powder;

a dispensing system adapted to selectively dispense both components of a two-part reactive resin onto said non-reactive powder;

~~a curing system configured to cure said reactive resin; and~~

a computing device coupled to and configured to control said dispensing system and said curing system.

25. (original) The solid freeform fabrication system of claim 24, wherein said powder spreading system comprises a mechanical roller.

26. (original) The solid freeform fabrication system of claim 25, wherein said mechanical roller is configured to planarize and pack a quantity of said non-reactive powder.

27. (original) The solid freeform fabrication system of claim 24, wherein said dispensing system comprises an inkjet dispenser.

28. (original) The solid freeform fabrication system of claim 27, wherein said inkjet dispenser comprises one of a thermal inkjet dispenser, a continuous inkjet dispenser, or a piezoelectric inkjet dispenser.

200310701-1

10/648,122

29. (currently amended) The solid freeform fabrication system of claim 27, wherein said inkjet dispenser comprises a plurality of ejection orifices configured to selectively eject both components parts of ~~[[a]]~~ said two-part reactive resin.

30. (currently amended) A solid freeform fabrication system for producing a three-dimensional object using non-reactive powder comprising:
spreading means for spreading successive layers of said non-reactive powder;
dispensing means for dispensing a reactive resin onto said non-reactive powder;
curing means for curing said reactive resin, wherein said curing means only partially cures a layer of reactive resin until at least one additional layer of non-reactive powder and selectively-dispensed reactive resin have been formed, said reactive resin then being fully cured so as to promote adhesion between layers of said object; and
controlling means for controlling said spreading means, said dispensing means, and said curing means.

31. (original) The solid freeform fabrication system of claim 30, wherein said spreading means comprises one of a blade or a mechanical roller.

32. (original) The solid freeform fabrication system of claim 30, wherein said dispensing means comprises a thermal inkjet dispenser.

33. (original) The solid freeform fabrication system of claim 30, wherein said dispensing means comprises one of a piezoelectric inkjet dispenser or a continuous inkjet dispenser.

34. (original) The solid freeform fabrication system of claim 30, wherein said curing means comprises a heater.

35. (original) The solid freeform fabrication system of claim 30, wherein said curing means comprises a UV radiation applicator.

200310701-1

10/648,122

36. (original) The solid freeform fabrication system of claim 30, wherein said controlling means comprises a computer.

37-49. (cancelled)

50. (new) The method of claim 2, wherein said reactive resin comprises an ultraviolet (UV) curable resin.

51. (new) The method of claim 2, further comprising dispensing said heated reactive resin directly onto said non-reactive powder on said substrate.

52. (new) The method of claim 2, further comprising applying ultrasonic energy to said mixture of reactive resin and non-reactive powder.

53. (new) The method of claim 2, wherein curing said reactive resin further comprises:
partially curing said reactive resin;
applying at least one other layer of non-reactive powder and selectively dispensed reactive resin; and
fully curing said reactive resin after said at least one other layer is formed to promote adhesion between layers of said object.

54. (new) The method of claim 3, wherein said reactive resin comprises an ultraviolet (UV) curable resin.

55. (new) The method of claim 3, further comprising dispensing said heated reactive resin directly onto said non-reactive powder on said substrate.

56. (new) The method of claim 3, wherein curing said reactive resin further comprises:
partially curing said reactive resin;

200310701-1

10/648,122

applying at least one other layer of non-reactive powder and selectively-dispensed reactive resin; and

fully curing said reactive resin after said at least one other layer is formed to promote adhesion between layers of said object.

57. (new) The solid freeform fabrication system of claim 24, further comprising a curing system for curing said two-part reactive resin.

58. (new) A method for creating a three-dimensional solid freeform fabrication object with non-reactive powder comprising:

spreading a non-reactive powder on a substrate;

selectively dispensing a reactive resin onto said non-reactive powder, forming a mixture of reactive resin and non-reactive powder, wherein said mixture defines said three-dimensional object;

partially curing said reactive resin;

applying at least one other layer of non-reactive powder and selectively-dispensed reactive resin; and

fully curing said reactive resin after said at least one other layer is formed to promote adhesion between layers of said object.

59. (new) A method for creating a three-dimensional solid freeform fabrication object with non-reactive powder comprising:

spreading a non-reactive powder on a substrate; and

selectively dispensing both components of a two-part reactive resin onto said non-reactive powder, forming a mixture of reactive resin and non-reactive powder, wherein said mixture defines said three-dimensional object.

60. (new) The method of claim 59, further comprising curing said two-part resin.

61. (new) The method of claim 59, further comprising allowing said components of said two-part reactive resin to react and harden said reactive resin.

200310701-1

10/648,122

62. (new) A system for fabricating a three-dimensional solid freeform fabrication object with non-reactive powder comprising:

a system for spreading a non-reactive powder on a substrate;

an inkjet dispenser for selectively dispensing a reactive resin onto said non-reactive powder, forming a mixture of reactive resin and non-reactive powder, wherein said mixture defines said three-dimensional object; and

a curing system for curing said reactive resin thereby encapsulating said non-reactive powder.

63. (new) The system of claim 62, wherein said curing system comprises an ultraviolet light source.

64. (new) The system of claim 62, further comprising a system for applying ultrasonic energy to said mixture prior to curing.